



TERMOREGULADORES CEMAUSA MOULD-MASTER II

MODELO	TM 12-90			TM 20-90				TM 35-90			TM 90 D9	TM 120 D9	TM 150 IN9	TM 20-200		TM 35-200		
SERIE	AGUA OPEN TANK			AGUA OPEN TANK				AGUA OPEN TANK			AGUA		AGUA PRESURIZADA	ACEITE OPEN TANK		ACEITE OPEN TANK		
TIPO	P3	P6	P9	P6	P9	P12	P18	P18	P24	P30	90	120	150	P6	P9	P18	P24	P30
POTENCIA CALORIFICA (kW)	3	6	9	6	9	12	18	18	24	30	9		9	6	9	18	24	30
POTENCIA MOTOR (kW)	0,5			0,5				0,5			0,45		0,5	0,5		0,5		
CAPACIDAD TANQUE (L)	12			20				35			NP	NP	NP	20		35		
BOMBA	VERTICAL EN DEPOSITO			VERTICAL EN DEPOSITO				VERTICAL EN DEPOSITO			HORIZONTAL		MAGNETICA	VERTICAL EN DEPOSITO		VERTICAL EN DEPOSITO		
REFRIGERACIÓN	INDIRECTA			INDIRECTA				INDIRECTA			DIRECTA		INDIRECTA	INDIRECTA		INDIRECTA		
TEMPERATURA MÁX. (°C)	90			90				90			90	120	150	200		200		
CAUDAL MÁXIMO (L / min)	60			60				60			70		40	60		60		
PRESIÓN MÁXIMA (BAR)	3,8			3,8				3,8			2,2	2,2	5	3,8		3,8		
TENSIÓN (V)	400 III			400 III				400 III			400 III		400 III	400 III		400 III		
FRECUENCIA (Hz)	50 / 60			50 / 60				50 / 60			50 / 60		50 / 60	50 / 60		50 / 60		
CONSUMO (A)	10	20	25	20	25	33	40	40	63	82	25	25	25	20	25	40	63	82
DIMENSIONES a x l x alt. (mm)	290 x 650 x 510			360 x 680 x 715				360 x 680 x 715			360 x 680 x 715		360 x 680 x 715	360 x 680 x 715		360 x 680 x 715		
PESO Kg	40			50				60			50		55	50		60		